



## Reynolds 953

Part	Loc	Diameter	Gauge	Length	Notes
953 frame tubes			Aged - Suffix "A"		
SS3900		25,4	0.5/0.3/0.5	600	40.40.380.40.100
SS4000		28,6	0.5/0.3/0.5	600	40.40.380.40.100
SS4010		28,6	0.5/0.3/0.5	600	75.50.280.50.145
SS4020		28,6	0.55/0.35/0.55	625	75.50.280.50.170
SS4070		28,6	0.6/0.4	635	125.75.435
SS4100		31,75	0.55/0.35/0.55	650	40.40.400.40.130
SS4110		31,75	0.6/0.4/0.6	650	40.40.400.40.130
SS4120		31,75	0.6/0.4/0.6	650	120.50.300.50.130
SS4130		31,75	0.55/0.35/0.55	650	120.50.300.50.130
SS4136		31,75	0.7/0.4/0.7	550	75.50.200.50.175
SS4141		31,75	0.7/0.4/0.7	635	75.50.200.50.260
SS4712	31.75/27.2 id		0.7/0.4/0.7	550	seat tube from SS4136
SS4713	31.75/27.2 id		0.7/0.4/0.7	635	seat tube from SS4141
SS4200	34,9		0.55/0.35/0.55	680	40.40.420.40.140
SS4210	34,9		0.6/0.4/0.6	680	40.40.420.40.140
SS4220	34,9		0.6/0.4/0.6	680	120.30.320.30.180
SS4230	34,9		0.65/0.45/0.65	680	120.30.320.30.180
SS4240	34,9		0.7/0.5/0.7	680	120.30.320.30.180
SS4300	36,4		0.6/0.45/0.6	685	120.50.300.50.165
Shaped Tubing			BASED ON PART		
SS4710	34.9->31.7		swaged 34.9mm	680	SS4220
SS4720	Teardrop 34.9		full length	680	SS4220
SS4730	31.7 OVAL		full length 35/26	635	SS4100
SS4732	31.7 Bi-Oval		90 degree opposed oval	650	SS4120
SS4740	34.9 OVAL		full length 40/30	680	SS4210
SS4742	34.9 Bi-Oval		90 degree opposed oval	680	SS4210
chainstay in 953 - butted					
FS4540	17.25/29.3 oval		0,5	420	taper to 15mm
FS4520	17.25/29.3 oval		0.7/0.5	410	taper to 15mm tip
FS4522	22,2		0,7	440	taper to 15mm tip cranked 10 degrees
FS4523	22,2		0,7	420	straight, taper to 15mm tip straight
FS4544	22,2		0.55	410	ROR taper to 15mm tip

# Feuille1

Part	Loc	Diameter	Gauge	Length	Notes
<b>Head tube in 953</b>					
HS4430		31,7	0,75	200	
HS4452		36,4	1,3	200	suplied in 17/4ph material
<b>SEATSTAYS IN 953 (not aged)</b>					
GS4650		19,05	0,6	560	D/taper to 13mm tip
GS4652		19,05	0,6	560	S/taper to 13mm tip
GS4670		16	0,7	560	S/taper to 13mm tip
GS4672		16	0,7	560	D/taper to 13mm tip
<b>Road Fork Blades</b>					
ES4800		27.5x20 oval	0,7	380	straight - 15mm tip
ES4810		27.5x20 oval	0,7	380	raked 16 x 30mm / 15 tip

## MIRROR FINISH POLISH

All 953 tubes can be supplied with a mirror finish polish

Minimum order 10 pieces

## FRAME FITTINGS

LS110	BB Shell	38.1mm, thread 24TPI, 68mm wide	17/4ph grade stainless
LS185	Rear Dropouts(PR)	universal style	17/4ph grade stainless
LS200	Cable guides	EA	EA 316L
LS210	STI bosses	set of 2	SET OF 2 316L
LS220	Campy bosses	set of 2	SET OF 2 316L
LS250	Brake bridge	Standard allen key fit	EA 304
LS260	Seat clamp	for 28.6mm OD	EA 304
LS265	Seat clamp	for 31.7mm OD	EA 304
SSWW17-1		1.2mm dia 17/4 grade x 910mm	EA 901
LS230	Integrated	head cups for 38.1 HT	