



## Basic geometry

	3XS	2XS	XS	S	M
Body Height in cm	≤ 160	160 - 166	166 - 172	172 - 178	≥ 178
Seat Height in mm (a)	593 - 693	623 - 723	653 - 753	683 - 783	713 - 813
Seat Tube Length in mm (b)	402	432	462	492	522
Top Tube Length in mm (c)	492	502	522	537	551
Head Tube Length in mm (d)	109	129	124	143	164
Head Tube Angle (e)	70°	70,8°	70,25°	72°	72,5°
Seat Tube Angle (f)	73,5°	73,5°	73,5°	73,5°	73,5°
Chainstay Length in mm (g)	415	415	415	415	415
Wheel Base in mm (h)	961	965	983	989	996
Stack in mm (i)	502	515	538	561	584
Reach in mm (j)	346	349	362	369	378
Stand-over Height in mm (k)	685	711	746	774	801
Bottom Bracket Offset in mm (l)	63	63	75	75	75

## Component geometry

	3XS	2XS	XS	S	M
Spacer in mm	27,5	27,5	27,5	27,5	27,5
Stem Length in mm	70	80	80	90	100
Handlebar Width in mm	380	380	380	400	400
Crank Length in mm	165,0	165,0	170,0	172,5	172,5
Chainring Size	50/34	50/34	50/34	50/34	50/34
Seat Post Diameter in mm	27,2	27,2	27,2	27,2	27,2
Seat Post Length in mm	350	350	350	350	350
Maximum Seat Post Insertion Depth in mm	207	207	207	207	207
Minimum Seat Post Insertion Depth in mm	107	107	107	107	107
Wheel Size	27.5"	27.5"	28"	28"	28"
Disc Size in mm	140 / 140	140 / 140	160 / 160	160 / 160	160 / 160