



Basis Geometrie

	2XS	XS	S	M	L	XL	2XL
Körpergrösse in cm	≤ 166	166 - 172	172 - 178	178 - 184	184 - 190	190 - 196	≥ 196
Sitzhöhe in mm (a)	639 - 714	666 - 766	696 - 796	726 - 826	756 - 856	786 - 886	816 - 916
Sitzrohrlänge in mm (b)	441	471	501	531	561	591	621
Oberrohrlänge in mm (c)	516	529	546	555	569	594	609
Steuerrohr in mm (d)	88	107	121	142	162	188	206
Lenkwinkel (e)	70°	71,2°	72,8°	73,25°	73,3°	73,5°	73,8°
Sitzrohrwinkel (f)	73,5°	73,5°	73,5°	73,5°	73,5°	73,5°	73,5°
Kettenstreben in mm (g)	410	410	410	410	413	415	415
Radstand in mm (h)	975	979	982	988	1.003	1.029	1.042
Stack in mm (i)	498	520	539	560	580	606	624
Reach in mm (j)	372	378	390	393	401	419	429
Überstandshöhe in mm (k)	720	748	775	801	828	851	874
Tretlager-Offset in mm (l)	70	70	70	70	70	70	70
Effektiver Stack in mm (o)	587	608	622	642	663	688	706
Effektiver Reach in mm (p)	517	535	549	563	580	598	619

Dimensionen Anbauteile

	2XS	XS	S	M	L	XL	2XL
Spacer in mm	20	20	20	20	20	20	20
Masse des Cockpits	80	90	90	100	110	110	120
Kurbellänge in mm	170,0	170,0	170,0	172,5	172,5	175,0	175,0
Kettenblattgrösse	52/36	52/36	52/36	52/36	52/36	52/36	52/36
Sattelstützenlänge in mm	291	313	313	313	313	313	313
Maximale Einschubtiefe der Sattelstütze in mm	141	166	166	166	166	166	166
Minimale Einschubtiefe der Sattelstütze in mm	66	66	66	66	66	66	66
Laufradgrösse	28"	28"	28"	28"	28"	28"	28"
Durchmesser Bremsscheibe in mm	140 / 140	140 / 140	160 / 140	160 / 140	160 / 140	160 / 160	160 / 160