

ARID CARBON RR SL

Midnight Blue / Denim Blue / Bunker Grey



- FRAME & FORK** STEALTH AIR CARBON • **GROUPSET** SRAM RED XPLR AXS 13s, CARBON POWERMETER CRANKS
• **WHEELS** ZIPP 303 XPLR SW • **TYRES** GOODYEAR XPLR 700x45mm • **HANDLEBAR** ONOFF S9 CARBON • **SEATPOST** ONOFF S9 CARBON
• **SADDLE** FIZIK VENTO ARGO 00 CARBON

ARID CARBON RR SL

Midnight Blue / Denim Blue / Bunker Grey

FRAME	Arid Stealth Air Carbon, in-tube storage, T47 bottom bracket, tapered head tube, HHG internal cable routing, 12x142mm rear axle, 1X drivetrain design, Flatmount brake compatible. Total system weight - including bike, rider, and equipment - should not exceed 130 kg (285 lbs)
SIZES	S: 410mm / M: 450mm / ML: 480mm / L: 510mm / XL: 540mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	Stealth Air Carbon tapered steerer tube, HHG, flat mount integrated fork
FORK REMOTE	--
HEADSET	Onoff IS52/IS52, 1-1/8", 1.5" head tube, sealed bearings, Internal cable routing.
STEM	Onoff Semi-Integrated, 31.8mm bar bore, rise: -7°, length: S size: 60mm, M size: 70mm, ML size: 70mm, L size: 80mm, XL size: 90mm
HANDLEBAR	OnOff S9 GR CARBON 16° bar flare. Width sizes S size: 440mm, M size: 440mm, ML size: 460mm, L size: 460mm XL size: 460mm
GRIPS	OnOff HEX Bartape
SEATPOST	Onoff S9 Carbon, diameter 27.2mm, length 400mm
SADDLE	FIZIK Vento Argo 00 140mm
FRONT BRAKE	Sram RED AXS 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
REAR BRAKE	Sram RED AXS 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
BRAKE LEVER	Sram RED, contact point adjustment, tooled reach adjust, carbon levers
RIMS	Zipp 303 XPLR SW, 32mm internal width, 54mm rim depth, hookless, infinity hubs, 24 spokes
SPOKES	CX-Ray - Black
FRONT HUB	ZR1 Disc Brake, 12x100mm, Centerlock
REAR HUB	ZR1 Disc Brake, 12x142mm, XDR 6 Pawls, Compression Springs, Centerlock. XD Freehub

FRONT TIRE	Goodyear XPLR Inter 700x45
REAR TIRE	Goodyear XPLR Inter 700x45
CRANKSET	Sram RED XPLR carbon, Power meter, DUB axle, thread-mount chainring, S size: 170mm M size: 170mm ML size: 172,5mm L size: 172,5mm XL size: 175mm, CL 47,5
RINGS	Sram 40T Thread Mount, alloy, narrow-wide
BOTTOM BRACKET	Sram DUB T47 BSA, sealed bearings, 85,5mm
PEDALS	--
CHAIN	Sram RED, 13s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram RED XPLR AXS, Magic wheel, cage lock, 1x13s,
SHIFT LEVERS	Sram Force Etap AXS 13s
CASSETTE	Sram XG-1391, 10-46T, 13s
MOTOR	--
BATTERY	--
DISPLAY	--
DERAILLEUR HANGER	--
OTHERS	--
WEIGHT	7,9 kg

ARID CARBON RR

Bunker Grey / Fog Grey / Flame Red



FRAME & FORK STEALTH AIR CARBON • **GROUPSET** SRAM FORCE XPLR ETAP AXS, CARBON POWERMETER CRANKS
• **WHEELS** MAVIC ALLROAD PRO CARBON SL • **HANDLEBAR** ONOFF S9 CARBON • **SEATPOST** ONOFF S9 CARBON
• **SADDLE** FIZIK VENTO ARGO X5, 140mm

ARID CARBON RR

Bunker Grey / Fog Grey / Flame Red

FRAME	Arid Stealth Air Carbon, in-tube storage, T47 bottom bracket, tapered head tube, HHG internal cable routing, 12x142mm rear axle, 1X drivetrain design, Flatmount brake compatible. Total system weight - including bike, rider, and equipment - should not exceed 130 kg (285 lbs)
SIZES	S: 410mm / M: 450mm / ML: 480mm / L: 510mm / XL: 540mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	Stealth Air Carbon tapered steerer tube, HHG, flat mount integrated fork
FORK REMOTE	--
HEADSET	Onoff IS52/IS52, 1-1/8", 1.5" head tube, sealed bearings, Internal cable routing.
STEM	Onoff Semi-Integrated, 31.8mm bar bore, rise: -7°, length: S size: 60mm, M size: 70mm, ML size: 70mm, L size: 80mm, XL size: 90mm
HANDLEBAR	OnOff S9 GR CARBON 16° bar flare. Width sizes S size: 440mm, M size: 440mm, ML size: 460mm, L size: 460mm XL size: 460mm
GRIPS	OnOff HEX Bartape
SEATPOST	Onoff S9 Carbon, diameter 27.2mm, length 400mm
SADDLE	FIZIK Terra Argo X5 140mm
FRONT BRAKE	SRAM Force Etap AXS 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
REAR BRAKE	Sram Force Etap AXS, 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
BRAKE LEVER	Sram Force, contact point adjustment, tooled reach adjust, plastic shift lever, LFRT brake lever
RIMS	Mavic Allroad Pro Carbon SL, UST, 25mm internal width, hookless, infinity hubs, 24 spokes
SPOKES	Mavic Steel double butted flat spokes
FRONT HUB	Mavic, 12x100mm, IS 6 bolts
REAR HUB	Mavic infinity hub, 12x142mm, XD ID360 Ratchet system, IS 6 bolts, XDR Freehub

FRONT TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
REAR TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
CRANKSET	SRAM Force 1 Carbon, Power meter, DUB axle, S size: 170mm M size: 170mm ML size: 172,5mm L size: 172,5mm XL size: 175mm, CL 47,5
RINGS	Sram X-Sync Eagle 40T direct mount, alloy, narrow-wide
BOTTOM BRACKET	Sram DUB T47 BSA, sealed bearings, 85,5mm
PEDALS	--
CHAIN	Sram Force, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram Force XPLR Etap AXS, 12s
SHIFT LEVERS	Sram Force Etap AXS 12s
CASSETTE	Sram XG-1271, 10-44T, 12s
MOTOR	--
BATTERY	--
DISPLAY	--
DERAILLEUR HANGER	Sram UDH
OTHERS	--
WEIGHT	8,8 kg

ARID CARBON R

Black / Nimbus Grey / Tonic Gold



FRAME & FORK STEALTH AIR CARBON • **GROUPSET** SRAM RIVAL ETAP AXS • **WHEELS** MAVIC ALLROAD SL • **TIRES** MAXXIS REAVER 700x45mm
• **HANDLEBAR** ONOFF S9 CARBON • **SEATPOST** ONOFF S9 CARBON • **SADDLE** FIZIK VENTO ARGO X5, 140mm

ARID CARBON R

Black / Nimbus Grey / Tonic Gold

FRAME	Arid Stealth Air Carbon, in-tube storage, T47 bottom bracket, tapered head tube, HHG internal cable routing, 12x142mm rear axle, 1X drivetrain design, Flatmount brake compatible. Total system weight - including bike, rider, and equipment - should not exceed 130 kg (285 lbs)
SIZES	S: 410mm / M: 450mm / ML: 480mm / L: 510mm / XL: 540mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	Stealth Air Carbon tapered steerer tube, HHG, flat mount integrated fork
FORK REMOTE	--
HEADSET	Onoff IS52/IS52, 1-1/8", 1.5" head tube, sealed bearings, Internal cable routing.
STEM	Onoff Semi-Integrated, 31.8mm bar bore, rise: -7°, length: S size: 60mm, M size: 70mm, ML size: 70mm, L size: 80mm, XL size: 90mm
HANDLEBAR	OnOff S9 GR CARBON 16° bar flare. Width sizes S size: 440mm, M size: 440mm, ML size: 460mm, L size: 460mm XL size: 460mm
GRIPS	OnOff HEX Bartape
SEATPOST	Onoff S9 Carbon 0-R, diameter 27.2mm, length 400mm
SADDLE	FIZIK Terra Argo X5 140mm
FRONT BRAKE	Sram Rival Etap AXS 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
REAR BRAKE	Sram Rival Etap AXS, 2 piece caliper, Paceline 160mm Centerlock rotor, steel-backed organic pad
BRAKE LEVER	Sram Rival, contact point adjustment, tooled reach adjust, plastic levers
RIMS	Mavic Allroad SL, UST, 25mm internal width, hookless, infinity hubs, 24 spokes
SPOKES	Mavic Steel double butted flat spokes
FRONT HUB	Mavic, 12x100mm, IS 6 bolts
REAR HUB	Mavic infinity hub, 12x142mm, XD ID360 Ratchet system, IS 6 bolts, XDR Freehub

FRONT TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
REAR TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
CRANKSET	Sram Rival 1 DUB GLS Wide, S size: 170mm M size: 170mm ML size: 172,5mm L size: 172,5mm XL size: 175mm, CL 47,5
RINGS	Sram X-Sync Eagle 40T direct mount, alloy, narrow-wide
BOTTOM BRACKET	Sram DUB T47 BSA, sealed bearings, 85,5mm
PEDALS	--
CHAIN	Sram Rival, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram Rival XPLR Etap AXS, 12s
SHIFT LEVERS	Sram Rival Etap AXS 12s,
CASSETTE	Sram XG-1251 10-44T, 12s
MOTOR	--
BATTERY	--
DISPLAY	--
DERAILLEUR HANGER	Sram UDH
OTHERS	--
WEIGHT	8,9 kg

ARID CARBON

Earth Red / Black / Flame Red



FRAME & FORK STEALTH AIR CARBON • **GROUPSET** SHIMANO GRX RX-610 • **WHEELS** MAVIC ALLROAD • **TIRES** MAXXIS REAVER 700x45mm
• **HANDLEBAR** ONOFF S3 ALLOY • **SEATPOST** ONOFF S9 CARBON • **SADDLE** FIZIK VENTO ARGO X5, 140mm

ARID CARBON

Earth Red / Black / Flame Red

FRAME	Arid Stealth Air Carbon, in-tube storage, T47 bottom bracket, tapered head tube, HHG internal cable routing, 12x142mm rear axle, 1X drivetrain design, Flatmount brake compatible. Total system weight - including bike, rider, and equipment - should not exceed 130 kg (285 lbs)
SIZES	S: 410mm / M: 450mm / ML: 480mm / L: 510mm / XL: 540mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	Stealth Air Carbon tapered steerer tube, HHG, flat mount integrated fork
FORK REMOTE	--
HEADSET	Onoff IS52/IS52, 1-1/8", 1.5" head tube, sealed bearings, Internal cable routing.
STEM	Onoff Semi-Integrated, 31.8mm bar bore, rise: -7°, length: S size: 60mm, M size: 70mm, ML size: 70mm, L size: 80mm, XL size: 90mm
HANDLEBAR	OnOff S3 GR 16° bar flare. Width sizes S size: 440mm, M size: 440mm, ML size: 460mm, L size: 460mm XL size: 460mm
GRIPS	OnOff HEX Bartape
SEATPOST	Onoff S9 Carbon 0-R, diameter 27.2mm, length 400mm
SADDLE	FIZIK Terra Argo X5 140mm
FRONT BRAKE	Shimano GRX RX-610, RX-400 caliper, CL-800 ice tech 160mm centerlock rotor, resin pad
REAR BRAKE	Shimano GRX RX-610, RX-400 caliper, CL-800 ice tech 160mm centerlock rotor, resin pad
BRAKE LEVER	Shimano GRX RX-610, contact point adjustment, tooled reach adjust, aluminium lever
RIMS	Mavic Allroad Disc, UST, 25mm internal width, hookless, infinity hubs, 24 spokes front, 28 spokes rear
SPOKES	Mavic Steel double butted flat spokes
FRONT HUB	Mavic, 12x100mm, IS 6 bolts
REAR HUB	Mavic infinity hub, 12x142mm, XD ID360 Ratchet system, IS 6 bolts, MS Freehub

FRONT TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
REAR TIRE	Maxxis Reaver 700x45, tubeless ready, dual compound EXO protection, 120 TPI, folding bead
CRANKSET	Shimano GRX RX-610, S size: 170mm M size: 170mm ML size: 172,5mm L size: 172,5mm XL size: 175mm, CL 49,7
RINGS	Shimano 40T, direct mount, steel
BOTTOM BRACKET	Token T47 BSA sealed bearings, 85,5mm
PEDALS	--
CHAIN	Shimano SLX M7100, Quick link
FRONT DERAILLEUR	--
REAR DERAILLEUR	Shimano GRX RX-822-GS, 12s
SHIFT LEVERS	Shimano GRX RX-610 dual control, alloy lever
CASSETTE	Shimano SLX M7100, hiperglide+, 10-45, 12s
MOTOR	--
BATTERY	--
DISPLAY	--
DERAILLEUR HANGER	Sram UDH
OTHERS	--
WEIGHT	9,7 kg

